

X3M EXTREME FLIGHT...BUSHING BEARING BLOCKS

X3M32/40

型番	シーブ径	ロープ最大径	THROAT	安全強度	破断強度	重量	形容	価格
	[mm]	[mm]	[mm]	[kg]	[kg]	[g]		[¥]
<b>X3M32S</b>	32	8	17	1500	3000	58	single (plug-in)	29100.
<b>X3M32SO</b>	32	8	17	1500	3000	58	single, snatch block	31700.
<b>X3M40S</b>	40	10	20	2000	4000	90	single (plug-in)	39950.
<b>X3M40SO</b>	40	10	20	2000	4000	90	single, snatch block	43600.
<b>X3M40Sln</b>	40	10	40	2000	4000	93	single (plug-in)	39950.
<b>X3M40SOln</b>	40	10	40	2000	4000	93	single, snatch block	43600.

X3M=extreme flight S=single SO=single swiveling ln=long loop



## X3M 46/50/55/60

型番	シーブ径	ロープ最大径	THROAT	安全強度	破断強度	重量	形容	価格
	[mm]	[mm]	[mm]	[kg]	[kg]	[g]		[¥]
<b>X3M46S</b>	46	12	25	3000	6000	155	single (plug-in)	52750.
<b>X3M46SO</b>	46	12	25	3000	6000	155	single, snatch block	56400.
<b>X3M46SIn</b>	46	12	40	3000	6000	155	single (plug-in)	52750.
<b>X3M46SOIn</b>	46	12	40	3000	6000	155	single, snatch block	56400.
<b>X3M50S</b>	50	14	30	4000	8000	210	single (plug-in)	63500.
<b>X3M50SO</b>	50	14	30	4000	8000	210	single, snatch block	68800.
<b>X3M50SIn</b>	50	14	45	4000	8000	205	single (plug-in)	63500.
<b>X3M50SOIn</b>	50	14	45	4000	8000	205	single, snatch block	68800.
<b>X3M55S</b>	55	16	30	5000	10000	245	single (plug-in)	74350.
<b>X3M55SO</b>	55	16	30	5000	10000	245	single, snatch block	78800.
<b>X3M55SIn</b>	55	16	50	5000	10000	249	single (plug-in)	74350.
<b>X3M55SOIn</b>	55	16	50	5000	10000	249	single, snatch block	78900.
<b>X3M60S</b>	60	18	35	6000	12000	420	single (plug-in)	85100.
<b>X3M60SO</b>	60	18	35	6000	12000	420	single, snatch block	92300.
<b>X3M60SIn</b>	60	18	35	6000	12000	430	single (plug-in)	85100.
<b>X3M60SOIn</b>	60	18	35	6000	12000	430	single, snatch block	92300.

X3M=extreme flight S=single SO=single swiveling In=long loop

## X3M 70/90/110/120

型番	シーブ径	ロープ最大径	THROAT	安全強度	破断強度	重量	形容	価格
	[mm]	[mm]	[mm]	[kg]	[kg]	[g]		[¥]
<b>X3M70S</b>	70	20	40	7000	14000	500	single (plug-in)	95950.
<b>X3M70SO</b>	70	20	40	7000	14000	500	single, snatch block	101300.
<b>X3M70SIn</b>	70	20	55	7000	14000	510	single (plug-in)	95950.
<b>X3M70SOIn</b>	70	20	55	7000	14000	510	single, snatch block	101300.
<b>X3M90S</b>	90	24	40	9000	18000	930	single (plug-in)	181500.
<b>X3M90SO</b>	90	24	40	9000	18000	930	single, snatch block	211700.
<b>X3M90SIn</b>	90	24	60	9000	18000	950	single (plug-in)	181500.
<b>X3M90SOIn</b>	90	24	60	9000	18000	950	single, snatch block	211700.
<b>X3M110S</b>	110	28	65	12000	24000	1500	single (plug-in)	267900.
<b>X3M110SO</b>	110	28	80	12000	24000	1500	single, snatch block	265200.
<b>X3M110SIn</b>	110	28	65	12000	24000	1540	single (plug-in)	267900.
<b>X3M110SOIn</b>	110	28	80	12000	24000	1540	single, snatch block	265200.
<b>X3M120S</b>	120	28	65	15000	30000	1700	single (plug-in)	376800.
<b>X3M120SO</b>	120	28	80	15000	30000	1700	single, snatch block	394000.
<b>X3M120SIn</b>	120	28	65	15000	30000	1740	single (plug-in)	376800.
<b>X3M120SOIn</b>	120	28	80	15000	30000	1740	single, snatch block	394000.

X3M=extreme flight S=single SO=single swiveling In=long loop